



# LiFe 10-48

## Lithium Ferro Phosphate

### 48V - 10Ah

#### Electrical Specifications

Nominal Voltage	48 V
Nominal Capacity @25°C , 0.2C	10 Ah
Working voltage range	42 to 54 V
Recommended charging voltage	53,5 to 54 V
Recommended charging current	Max. 5A
Max. continue discharge current	10A
Max. peak discharge current	12A for 30 sec
Discharging Cut-off voltage	42 V


#### Other Specifications

Cycle life (@20°C 0.2°C 80%DOD)	>= 4000 cycles
Dimensions LxWxH/mm (± 2mm)	442x285x44
Operating temperature (Discharge)	-30 °C to 60 °C
Operating temperature (Charge)	-20 °C to 60 °C
Storage temperature	-5 °C to 55 °C
Storage duration	12 mo +20 °C
Round trip efficiency (%)	> 98 %
Terminal	DSTB8-2-M5
Weight (kg)	7,9 (±0,2) kg
Safety standard on cell level	UL1642

#### Innovative Features

- RS485 communication output for monitoring
- Built-in BMS with charging current limitation
- Built-in automatic protection for over-charge, over-discharge and over-temperature conditions
- State of charge and state of health indication
- Built-in battery control for efficient operation
- Internal cell balancing
- Compatible with standard Telecom rectifiers and Energy storage systems
- Customized BMS function and parameters
- Maintenance free

#### Graphics



Revision: EN2019/10-0

Your Wing Dealer :

Wetac Stand-by bv (NL)	orderdesk@wetac.nl	00 31 (0)318 696 190
Wetac Stand-by bv (CZ)	standby@wetac.com	00 420 732 172 800
Wetac UK Ltd.	technicaluk@wetac.com	00 44 (0)1204 366 728
BSOL Batteriesysteme GmbH	info@bsol.de	00 49 (0)2173 330 330
Wetac Swiss GmbH	rcastiglione@wetac.ch	00 41 61 643 7066

