LiFe 70-48

Lithium Ferro Phosphate

48V - 70Ah

Electrical Specifications

Nominal Voltage	48 V
Nominal Capacity @25°C , 0.2C	70 Ah
Working voltage range	42 to 54 V
Recommended charging voltage	53,5 to 54 V
Recommended charging current	Max. 30A
Max. continue discharge current	70A
Max. peak discharge current	102A - 122A for 30 sec
	123A - 150A for 2 sec
Discharging Cut-off voltage	42 V

Innovative Features

- RS232, RS485 communication output for monitoring
- Built-in BMS with charging current limitation
- Built-in automatic protection for over-charge, over-discharge and over-temperature conditions
- State of charge and state of health indication
- Built-in battery control for efficient operation
- Internal cell balancing
- Compatible with standard Telecom rectifiers and Energy storage systems
- DO interface for customized dry contact signal
- PRO interface for upgrading BMS-firmware
- Customized BMS fuction and parameters
- Maintenance free

Other Specifications

Cycle life (@20°C 0.2°C 80%DOD)	>= 4000 cycles
Dimensions LxWxH/mm (± 2mm)	442x400x135
Operating temperature (Discharge)	-30 ℃ to 60 ℃
Operating temperature (Charge)	-20 ℃ to 60 ℃
Storage temperature	-5 ℃ to 55 ℃
Storage duration	12 mo +20 ℃
Round trip efficiency (%)	> 98 %
Terminal	DSTB22-2-2-M6
Weight (kg)	37 (±0,3) kg
Safety standard on cell level	UL1642

Graphics





Revision: EN2020-11

Your Wing Dealer :

Wetac Stand-by bv (NL)	orderdesk@wetac.nl	00 31 (0)318 696 190
Wetac Stand-by bv (CZ)	standby@wetac.com	00 420 732 172 800
Wetac UK Ltd.	technicaluk@wetac.com	00 44 (0)1204 366 728
BSOL Batteriesysteme GmbH	info@bsol.de	00 49 (0)2173 330 330
Wetac Swiss GmbH	info@wetac.ch	00 41 61 643 7066
Wetac Hellas S.A.	info@wetac.gr	00 30 6932 400322