



AUTOTRONIC 25 BOOST 230V 12V/24V



Tronic

12V

24V

Pb-Ca

Wet

Gel

AGM

EFB

MF

Overview

AUTOTRONIC 25 BOOST 230V 12V/24V

cod. 807540

Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage.

Fit with switches to choose either anormal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE).

The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM/START-STOP), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET).

Characteristics:

- * choice of output voltage, type of charge, charging mode

- * display of charging current

- * protection against overloads and polarity reversal.



1 PH 230V



CAR



BOAT



TRACTOR



VAN



CE MARKING



EAC CERTIFICATION



TÜV SUD CERTIFICATION

Technical data



CODE 807540



MAINS VOLTAGE 230 V - 1 ph 50/60Hz



CHARGING ABSORBED POWER 300 W



AUTOTRONIC 25 BOOST 230V 12V/24V



CHARGING VOLTAGE 12 / 24 V



EFFECTIVE CHARGING CURRENT 18 / 12 A



RATED CHARGE CURR. EN60335-2-29 12 / 8 A



MIN./MAX RATED REFERENCE CAPACITY 30/225 - 12V Ah



MIN./MAX RATED REFERENCE CAPACITY 20/180 - 24V Ah



ADJUSTMENT POSITIONS 4



DIMENSIONS 22,5 - 29 - 20,5 cm



WEIGHT 7,2 kg



EAN CODE 800489764142 3



PIECES/PALLET 56 pz/pallet



PIECES/PALLET - B 42 pz/pallet - B

Included Accessories



COLORADO 40B WORK CLAMP 40A - 712624



COLORADO 40R POSITIVE CLAMP 40A - 712623

POSITIVE CABLE 2,5 MMQ 1,5 M - 123986

WORK CABLE 2,5 MMQ 1,5 M - 123985