



STARTRONIC 530 230V



Pulse
Tronic

STAND-BY
FUNCTION

SAFE
(*)
START

6V

12V

24V

Pb-Ca

Wet

Gel

AGM

EFB

Overview

STARTRONIC 530 230V

cod. 829034

Digital, microprocessor controlled battery charger, maintainer and starter for charging all types of batteries (GEL/AGM/START-STOP), with 6/12/24V voltage and starting of cars, vans and trucks.

Startronic protects the on-board electronic such as ABS, airbag, electronic injection, etc.

Running modes: TEST, CHARGE, TRONIC, START and STAND-BY.

The STAND-BY function is activated through connection to the cigarette lighter outlet of the car, it allows to disconnect and charge the car battery without erasing the preset values of the on-board computer.

The TRONIC function allows for the electronic control of charging current, automatic interruption and restart.

The new implemented technology SAFE START does not damage the on-board electronics during the starting phase (START) because it eliminates the overvoltages typical of the traditional starters.

Features:

- choice of charge current 1÷40A
- display to check battery voltage, charging current and time
- display to check battery status
- protection against reverse polarity, battery failure, thermostatic interruption, faulty battery charger.



1 PH 230V



MOTORCYCLE



CAR



BOAT



TRACTOR



SMALL VAN



TRUCK



EXCAVATOR



VAN



CE MARKING



EAC CERTIFICATION


















TÜV SUD CERTIFICATION



STARTRONIC 530 230V

Technical data

 CODE	CODE 829034	 MAINS VOLTAGE 230 V - 1 ph 50/60Hz	 CHARGE/START POWER 1,5 / 9,5 kW
 CHARGING VOLTAGE 6 / 12 / 24 V	 CURRENT RANGE 1 - 40 A	 EFFECTIVE CHARGING CURRENT 75 A	
 RATED CHARGE CURR. EN60335-2-29 40 A	 START CURRENT 1V/C EN60335-2-29 300 A	 MAX STARTING CURRENT 400 A	
 MIN./MAX RATED REFERENCE CAPACITY 10 / 600 Ah	 DIMENSIONS 39 - 26 - 23 cm	 WEIGHT 19,5 kg	
 EAN CODE 800489771274 1	 PIECES/PALLET 18 pz/pallet	 PIECES/PALLET - B 12 pz/pallet - B	

Included Accessories

CABLE 16 MMQ 2 M - DINSE 25 - 123435



COLORADO 150B WORK CLAMP 150A - 712001



COLORADO 150R POSITIVE CLAMP 150A - 712002